



1-Needle Compound Feed Walking Foot Sewing Machines
Longarm 25" (635mm) with Built-in Bobbin Winder



- Mod. EM-1541-25** longarm 25" (635mm)
- EM-1541-25-FL** with pneumatic auto foot lifter
- EM-1541-25-BT** with automatic backtack and foot lifter

FEATURE:

- With the adoption of a new rectangular feed mechanism, an alternating vertical movement mechanism and a unision-feed mechanism, the machine can feed heavy material powerfully and smoothly. Well tensed seams are consistently produced without pitch errors.
- The machine has adopted a dual-tension mechanism, with which the machine can support.
- High-tension sewing with thick thread. This means that the machine produces seams of excellent quality on a broader range of materials, extending from light-to heavy-weight.
- With 9mm maximum stitch length, 36mm needle bar stoke, and 175mm extra large steel hand-wheel, the machine supports the sewing of extra heavy materials.



Auto reverse



Auto foot lifter

Max. sewing speed	1,800 s.p.m.	Working space	635 mm (25")
Max. stitch length	9 mm	Needle to be used	DPx17 #23
Lift of the presser foot	9 mm by Hand 16 mm by Knee	Needle system	#20 ~ #25
Alternating vertical movement	2.5~6.5 mm	Thread	#30 ~ #5
Needle bar stroke	36 mm	Motor to be used	Clutch Motor, 1/2HP,4P