

Made in Taiwan

1-Needle Unison Feed Flatbed Lockstitch Sewing Machine



models :

EM-1508NH

with automatic lubricating

EM-1508NH-T

for thick thread (#0)

EM-1508NH-FL

with pneumatic auto-lifter

EM-1508NH-BT

with automatic backtack and auto-lifter



Features:

- * With the adoption of a new complete rectangular feed mechanism, an alternating vertical movement mechanism, and a unison-feed mechanism, the machine can feed heavy materials for industrial use, such as cargo handling belts, car seat, sofas, and bags.
- * The maximum stitch length is 9mm, the needle bar stroke is 38mm. and an extra large steel hand-wheel with a diameter as large as 175mm, the machine supports the sewing of extra heavy materials.



Safety Clutch



16mm



SPECIFICATIONS

Max. sewing speed	2,500 s.p.m.	Working space	255 mm / 635mm
Max. stitch length	9 mm	Needle to be used	DPx17 #23
Lift of the presser foot	9 mm by Hand 16 mm by Knee	Needle system	#20 ~ #25
Alternating vertical movement	2.5~6.5 mm	Thread	#20 ~ #1
Needle bar stroke	38 mm	Motor to be used	Clutch Motor, 1/2HP,4P



Long arm 25" (635mm) work space

models :

EM-1508NH-25

with automatic lubricating for thick thread (#0)

EM-1508NH-25-T

with pneumatic auto-lifter

EM-1508NH-25-FL

EM-1508NH-25-BT

with automatic backtack and auto-lifter